

PowerDepot H5B

PowerDepot H5B is a low-voltage product for residential energy storage. It supports 5 units in parallel and has a capacity range from 5.12kWh to 25.6kWh. High safety and long lifespan to meet the long-term power needs of users.



Flexible Expansion

Up to 5 units in parallel,
5.12kWh—25.6kWh capacity



Automatic Self-heating

-20°C to 55°C operating temperature
(optional)



IP65 Protection

Fearless of outdoor insatallition,
strong environmental adaptability



Easy Installation

Support wall-mounted, floor-mounted
installations, high space utilization



Battery Equalization

Support extreme mixing of modules
at 0% and 100% charge



All-round Safety

Short-circuit lockout, surge-resistant,
safe and reliable

Model	PowerDepot H5B
Battery Type	LiFePO ₄
Nominal Battery Energy	5.12kWh
Operating voltage	44.8~57.6V
Nominal Voltage	51.2V
Nominal Capacity	100Ah
Max. output power	3.84kW
Recomended Charge & Discharge C Rate	0.5C
Recommended Charge/Discharge Current	50A
Recommended Depth of Discharge (DOD)	90%
Net Weight	59kg
Dimension[W*D*H]	574*228*600 mm
Charging Temp. Range	0~55°C/~20~55°C (with heating function)
Discharging Temp. Range	-20~55°C
Communication	CAN/RS485
Cycle Life *	≥6000 Cycles
Protection Level	IP65
Expansion	Up to 5 units in parallel
Color	White
Alarms	Overcharge/Over-discharge/Overcurrent/Overtemperature/ShortCircuit
Monitoring & Protection	Each system has smart BMS, breaker embedded in system
Pros	Can be used in both off-grid and hybrid setups, compact design, floor or wall-mounted
Certification & Safety Standard	UN38.3/CE-EMC/IEC62619/IEC62040/GOST-R/UKCA/CEC
Compatible Inverters	Solis/Deye/Luxpower/Voltronic/Hoymiles/Growatt/Goodwe/SMA/Victron/Ingeteam/Delios/SAJ/APS etc.

* Test conditions: 0.2C Charging & Discharging. @25°C, 90% DOD
Note: This specification is only suitable for Southeast Asia

